

View Online at <https://aerobasegroup.com/nsn/5320-01-547-5055>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.530 inches and 0.550 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.064 inches and 0.074 inches

**Width Between Flats:**

Between 0.079 inches and 0.080 inches

**Shank Diameter:**

Between 0.188 inches and 0.189 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.357 inches and 0.377 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.432 inches and 0.442 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

5380 double pounds per square inch

**Product Name:**

Pin-rivet, threaded

**Special Features:**

Color code light blue on thread end

**Material:**

Titanium alloy

**Material Specification:**

Ams4928 or ams4967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Hi-kote 1 per (73197) specification 294 mfr ref single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0