

View Online at <https://aerobasegroup.com/nsn/5320-01-547-5240>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.559 inches and 0.579 inches

Head Style:

Straight pan

Head Height:

Between 0.080 inches and 0.090 inches

Width Between Flats:

Between 0.095 inches and 0.097 inches

Shank Diameter:

Between 0.249 inches and 0.250 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.182 inches and 0.192 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

9300 double pounds per square inch

Product Name:

Pin-rivet, threaded

Special Features:

Color code light blue on thread end

Material:

Titanium alloy

Material Specification:

Ams4928 or ams4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-kote 1 per (73197) specification 294 mfr ref single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0