NSN 5320-01-547-5264

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style: Straight pan Head Height:

Thread Direction:

Fastener Length:

Between 1.973 inches and 1.993 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-547-5264

Between 0.130 inches and 0.140 inches
Width Between Flats:
Between 0.158 inches and 0.162 inches
Shank Diameter:
Between 0.374 inches and 0.375 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.641 inches and 0.676 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 1.558 inches and 1.568 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.375 inches
Shear Strength:
21000 double pounds per square inch
Product Name:
Pin-rivet, threaded
Special Features:
Color code light blue on thread end
Material:
Titanium alloy
Material Specification:
Ams4928 or ams4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Hi-kote 1 per (73197) specification 294 mfr ref single treatment response

NSN 5320-01-547-5264

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A528u0