## NSN 5320-01-547-5308

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-547-5308

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.020 inches and 1.040 inches
Head Style:
Straight pan
Head Height:
Between 0.037 inches and 0.047 inches
Width Between Flats:
Between 0.079 inches and 0.080 inches
Shank Diameter:
0.163 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.242 inches and 0.262 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.745 inches and 0.755 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.164 inches
Shear Strength:
4010 double pounds per square inch
Product Name:
Pin-rivet, threaded; (73197)hi-lite st pin, protruding shear head titanium 1/16" grip variation
Special Features:
Color code orange on thread end
Material:
Titanium alloy
Material Specification:
Ams4928 or ams4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Hi-kote 1, cage 73197 mfr ref single treatment response
Thread Series Designator:
Unic

Unjc

## NSN 5320-01-547-5308

Pin-rivet - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0