

View Online at <https://aerobasegroup.com/nsn/5320-01-547-5402>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.958 inches and 0.978 inches

Head Style:

Straight pan

Head Height:

Between 0.080 inches and 0.090 inches

Width Between Flats:

Between 0.095 inches and 0.097 inches

Shank Diameter:

Between 0.249 inches and 0.250 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.683 inches and 0.693 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

12660 double pounds per square inch

Product Name:

Pin-rivet, threaded; (73197)hi-lite st pin, protruding tension head, nickel base alloy

Special Features:

Color code green on thread end

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-kote 1 (73197) spec.294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0