

NSN 5320-01-547-5422 Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-547-5422 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Green

**Fastener Length:** 

Between 1.093 inches and 1.113 inches

**Head Style:** 

Flush countersunk

Width Between Flats:

Between 0.079 inches and 0.081 inches

**Shank Diameter:** 

Between 0.189 inches and 0.190 inches

**Shank Style:** 

Pin-rivet, straight, threaded

**Head Major Diameter:** 

Between 0.377 inches and 0.381 inches

Lubrication:

Cetyl alcohol

**Grip Length:** 

Between 0.809 inches and 0.818 inches

Thready Qty Per Inch (tpi):

32

**Thread Size:** 

0.191 inches

**Shear Strength:** 

7060 double pounds per square inch

**Countersink Angle:** 

100.0 degrees

**Collar Style:** 

Threaded break off type

**Product Name:** 

Hi-lite st pin

**Special Features:** 

Nas code for this item is nas nasm24694

Material:

Nickel alloy

**Material Specification:** 

Sae ams 5662m assn standard single material response

**Surface Treatment:** 

Paint threads

## NSN 5320-01-547-5422

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A528u0