

View Online at <https://aerobasegroup.com/nsn/5320-01-547-5422>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Identification Code Color:**

Green

**Fastener Length:**

Between 1.093 inches and 1.113 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.079 inches and 0.081 inches

**Shank Diameter:**

Between 0.189 inches and 0.190 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.377 inches and 0.381 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.809 inches and 0.818 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.191 inches

**Shear Strength:**

7060 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Collar Style:**

Threaded break off type

**Product Name:**

Hi-lite st pin

**Special Features:**

Nas code for this item is nas nasm24694

**Material:**

Nickel alloy

**Material Specification:**

Sae ams 5662m assn standard single material response

**Surface Treatment:**

Paint threads

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0