

View Online at <https://aerobasegroup.com/nsn/5320-01-547-5738>

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.030 inches and 1.050 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.079 inches and 0.080 inches

**Shank Diameter:**

Between 0.189 inches and 0.190 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.377 inches and 0.381 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.745 inches and 0.755 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Shear Strength:**

7060 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-rivet, threaded; (73197) hi-lite st pin 100 degree flush ms24694 tension head

**Special Features:**

Color code green on thread end

**Material:**

Nickel alloy

**Material Specification:**

Ams5662 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Hi-kote 1 (73197) spec.294 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0