

View Online at <https://aerobasegroup.com/nsn/5320-01-547-5738>

Thread Direction:

Right-hand

Fastener Length:

Between 1.030 inches and 1.050 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

Between 0.189 inches and 0.190 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.377 inches and 0.381 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.745 inches and 0.755 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

7060 double pounds per square inch

Countersink Angle:

100.0 degrees

Product Name:

Pin-riquet, threaded; (73197) hi-lite st pin 100 degree flush ms24694 tension head

Special Features:

Color code green on thread end

Material:

Nickel alloy

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-kote 1 (73197) spec.294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0