NSN 5320-01-548-1275



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-548-1275 Fastener Length: 0.925 inches **Head Style:** Cone **Head Height:** Between 0.063 inches and 0.070 inches **Shank Diameter:** Between 0.197 inches and 0.198 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Head Major Diameter:** Between 0.396 inches and 0.406 inches **Head Minor Diameter:** 0.375 inches **Expansion Device:** Threaded stem Lubrication: Dry film or paraffin wax or cetyl alcohol **End Application:** Aircraft, osprey v-22a, marine corps **Grip Length:** Between 0.250 inches and 0.300 inches **Product Name:** Inavy: rivet, blind: drawing: accu-lok blind fastener for composite application, low profile protruding head, titanium **Special Features:** Nut and stem are heat treated to 175 ksi tensile strength; includes astm d4181 acetal insert; drycap is mild steel - gray color Material: Titanium alloy nut **Material Specification:** Ams5639, type 304 assn standard single material response sleeve **Surface Treatment:** Aluminum stem **Surface Treatment Specification:** Nas4006 assn standard single treatment response nut

Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

Fiig:

A040a0