

View Online at <https://aerobasegroup.com/nsn/5320-01-551-6164>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.955 inches and 1.975 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.130 inches and 0.140 inches

**Width Between Flats:**

Between 0.197 inches and 0.217 inches

**Shank Diameter:**

Between 0.389 inches and 0.390 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.565 inches and 0.600 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

C-5 aircraft

**Grip Length:**

Between 1.370 inches and 1.385 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180 pounds per square inch

**Thread Size:**

0.375 inches

**Material:**

Steel comp e4340

**Material Specification:**

Mil-s-5000 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2. Cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.