NSN 5320-01-551-9146

Pin-rivet - Page 1 of 2



AeroBase

Group

View Online at https://aerobasegroup.com/nsn/5320-01-551-9146

| Thread Class: |
|---|
| 3a |
| Fastener Length: |
| Between 0.887 inches and 0.897 inches |
| Head Style: |
| Flush countersunk |
| Head Height: |
| Between 0.010 inches and 0.015 inches |
| Width Between Flats: |
| Between 0.104 inches and 0.119 inches |
| Shank Diameter: |
| Between 0.2021 inches and 0.2026 inches |
| Head Major Diameter: |
| Between 0.3486 inches and 0.3536 inches |
| Lubrication: |
| Cetyl alcohol |
| End Application: |
| C-17 aircraft |
| Grip Length: |
| Between 0.557 inches and 0.567 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Thread Size: |
| 0.190 inches |
| Countersink Angle: |
| 100.0 degrees |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams4967 assn standard single material response |
| Surface Treatment: |
| Aluminum |
| Surface Treatment Specification: |
| Per hi-shear specification no 294 mfr ref single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |

NSN 5320-01-551-9146

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

