

View Online at <https://aerobasegroup.com/nsn/5320-01-551-9790>

Thread Class:

M3a

Thread Direction:

Right-hand

Fastener Length:

0.875 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3271 inches and 0.3276 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.454 inches and 0.467 inches

Lubrication:

Cetyl alcohol

End Application:

C-17a aircraft

Grip Length:

0.375 inches

Thready Qty Per Inch (tpi):

B24

Thread Size:

0.3125 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet

Special Features:

Finish also has aluminum pigmented coating; heat treat 95 ksi fsu min; 160-180 ksi ftu per mil-h-81200

Material:

Titanium alloy

Material Specification:

Ams4967 assn standard single material response or ams4928 assn standard single material response

Surface Treatment:

Chromate and aluminum

Surface Treatment Specification:

Dps 4.50-197 (hi-kote 1 only) mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0