NSN 5320-01-552-3281

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-552-3281

0.620 inches Head Style: Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.124 inches and 0.129 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: 0.196 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.172 inches and 0.266 inches Shear Strength: 450 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Q-q-a-430 federal specification single material response stem Surface Treatment: Anodize
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.124 inches and 0.129 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: 0.196 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.172 inches and 0.266 inches Shear Strength: 450 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Shank Diameter: Between 0.124 inches and 0.129 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: 0.196 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.172 inches and 0.266 inches Shear Strength: 450 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Between 0.124 inches and 0.129 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: 0.196 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.172 inches and 0.266 inches Shear Strength: 450 single pounds per square inch Countersink Angle: Between 9.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Shank Style: Self-plugging mechanically locked stem Head Major Diameter: 0.196 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.172 inches and 0.266 inches Shear Strength: 450 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Self-plugging mechanically locked stem Head Major Diameter: 0.196 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.172 inches and 0.266 inches Shear Strength: 450 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Head Major Diameter: 0.196 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.172 inches and 0.266 inches Shear Strength: 450 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
0.196 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.172 inches and 0.266 inches Shear Strength: 450 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Expansion Device: Serrated stem-type w Grip Length: Between 0.172 inches and 0.266 inches Shear Strength: 450 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Serrated stem-type w Grip Length: Between 0.172 inches and 0.266 inches Shear Strength: 450 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Grip Length: Between 0.172 inches and 0.266 inches Shear Strength: 450 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Between 0.172 inches and 0.266 inches Shear Strength: 450 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Shear Strength: 450 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
450 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Between 99.0 degrees and 101.0 degrees Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Material: Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Aluminum sleeve Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Material Specification: Qq-a-430 federal specification single material response stem Surface Treatment:
Qq-a-430 federal specification single material response stem Surface Treatment:
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response stem or mil-c-5541 military specification single treatment response stem
Specification Data:
80205-nas1719 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-a-8625 spec.