NSN 5320-01-559-0687

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-559-0687 **Thread Class:** За **Thread Direction:** Right-hand **Head Style:** Flush countersunk **Shank Diameter:** Between 0.1810 inches and 0.1840 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.2966 inches and 0.3016 inches Lubrication: Cetyl alcohol **End Application:** Awacs aircraft **Grip Length:** 0.750 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 6130 double pounds per square inch **Countersink Angle:** 100.0 degrees **Collar Style:** Threaded break off type Material: Stainless steel **Material Specification:** Ams5737 assn standard single material response or ams5731 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-559-0687

Pin-rivet - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A528u0