# NSN 5320-01-559-7654

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-559-7654

## Thread Class:

3a

**Thread Direction:** 

Right-hand

## Fastener Length:

Between 1.785 inches and 1.825 inches

#### Head Style:

Countersunk w/reverse chamfer

#### **Head Height:**

Between 0.042 inches and 0.050 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.298 inches and 0.312 inches

#### Grip Length:

Between 1.501 inches and 1.562 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

## Shear Strength:

156000 single pounds per square inch

Material:

Steel comp h11

## **Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

#### Surface Treatment:

Nickel and cadmium

## Surface Treatment Specification:

Ams 2416 assn standard single treatment response

#### **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas4450 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5320-01-559-7654

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

