NSN 5320-01-559-9308

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-559-9308 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.003 inches and 1.023 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.189 inches and 0.190 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.297 inches and 0.302 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **End Application:** F-15 aircraft **Grip Length:** Between 0.683 inches and 0.693 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 7060 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** White paint on head Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

NSN 5320-01-559-9308

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0