

View Online at <https://aerobasegroup.com/nsn/5320-01-560-6602>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.160 inches and 1.180 inches

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

0.143 inches

**Width Between Flats:**

Between 0.127 inches and 0.129 inches

**Shank Diameter:**

Between 0.327 inches and 0.328 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

0.634 inches

**Lubrication:**

Solid film or dry film and cetyl alcohol

**Grip Length:**

0.630 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Shear Strength:**

125000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0