NSN 5320-01-562-1371

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

Between 2.018 inches and 2.038 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-562-1371

Head Style:		
Countersunk w/reverse chamfer		
Head Height:		
Between 0.004 inches and 0.008 inches		
Width Between Flats:		
Between 0.197 inches and 0.217 inches		
Shank Diameter:		
Between 0.389 inches and 0.390 inches		
Shank Style:		
Pin-rivet, straight, threaded		
Head Major Diameter:		
0.576 inches		
Lubrication:		
Cetyl alcohol, specification 305, hi-shear corp		
End Application:		
C-5 aircraft		
Grip Length:		
Between 1.433 inches and 1.443 inches		
Thready Qty Per Inch (tpi):		
24		
Min. Tensile Strength (psi):		
180 pounds per square inch		
Thread Size:		
0.375 inches		
Shear Strength:		
28 double pounds per square inch		
Countersink Angle:		
100.0 degrees		
Product Name:		
100 degree flush crown shear head alloy steel		
Material:		
Steel comp 4140		
Material Specification:		
Mil-s-5626 military specification single material response		
Surface Treatment:		
Cadmium		

NSN 5320-01-562-1371

Pin-rivet - Page 2 of 2



Surface	Treatment	Specification:
---------	------------------	----------------

Qq-p-416 type ii. Class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.