

View Online at <https://aerobasegroup.com/nsn/5320-01-562-1371>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.018 inches and 2.038 inches

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

Between 0.004 inches and 0.008 inches

**Width Between Flats:**

Between 0.197 inches and 0.217 inches

**Shank Diameter:**

Between 0.389 inches and 0.390 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

0.576 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

C-5 aircraft

**Grip Length:**

Between 1.433 inches and 1.443 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180 pounds per square inch

**Thread Size:**

0.375 inches

**Shear Strength:**

28 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Product Name:**

100 degree flush crown shear head alloy steel

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 type ii. Class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5626 spec.