

View Online at <https://aerobasegroup.com/nsn/5320-01-562-5566>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.580 inches and 1.600 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.130 inches and 0.140 inches

**Width Between Flats:**

Between 0.197 inches and 0.217 inches

**Shank Diameter:**

0.391 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.565 inches and 0.600 inches

**End Application:**

C-5 aircraft

**Grip Length:**

Between 0.995 inches and 1.005 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

210 pounds per square inch

**Thread Size:**

0.375 inches

**Shear Strength:**

25 double pounds per square inch

**Product Name:**

Pin rivet

**Material:**

Steel comp 8740

**Material Specification:**

Mil-s-6049 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 type ii.Class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.