NSN 5320-01-562-5570

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-562-5570

View Online at https://aerobasegroup.com/nsn/5320-01-562-5570
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 2.018 inches and 2.038 inches
Head Style:
Straight pan
Head Height:
Between 0.130 inches and 0.140 inches
Width Between Flats:
Between 0.197 inches and 0.217 inches
Shank Diameter:
0.391 inches
Head Major Diameter:
Between 0.565 inches and 0.600 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
End Application:
C-5 aircraft
Grip Length:
Between 1.432 inches and 1.442 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180 pounds per square inch
Thread Size:
0.375 inches
Shear Strength:
25 double pounds per square inch
Product Name:
Pin rivet
Material:
Steel comp 8740
Material Specification:
Mil-s-6049 military specification single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 type ii.Class 2 federal specification single treatment response
Thread Series Designator:

Unjf

NSN 5320-01-562-5570

Pin-rivet - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A528u0

Mil-std (military Standard):

Mil-s-6049 spec.