

View Online at <https://aerobasegroup.com/nsn/5320-01-562-5635>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.305 inches and 2.325 inches

Head Style:

Straight pan

Head Height:

Between 0.150 inches and 0.160 inches

Width Between Flats:

Between 0.233 inches and 0.253 inches

Shank Diameter:

Between 0.451 inches and 0.453 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.641 inches and 0.676 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

C-5 aircraft

Grip Length:

Between 1.620 inches and 1.630 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

180000 pounds per square inch

Thread Size:

0.437 inches

Shear Strength:

34800 double pounds per square inch

Product Name:

Pin rivet

Material:

Steel comp 8740

Material Specification:

Mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii. Class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.