NSN 5320-01-562-8781

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-562-8781

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
0.875 inches
Head Style:
Flush countersunk
Width Between Flats:
0.081 inches
Shank Diameter:
0.160 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
0.331 inches
End Application:
V1h-1n helicopter
Grip Length:
0.563 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.164 inches
Shear Strength:
4010 double pounds per square inch
Countersink Angle:
100.0 degrees
Product Name:
Pin 100 degree flush, tension head alloy steel
Material:
Steel comp 8740
Material Specification:
Mil-s-6049 military specification single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 type ii. Class 2 federal specification single treatment response
Thread Series Designator:
Unjc

NSN 5320-01-562-8781

Pin-rivet - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A528u0	

Mil-std (military Standard):

Mil-s-6049 spec.

Shelf Life: