

View Online at <https://aerobasegroup.com/nsn/5320-01-562-8796>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.700 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

0.081 inches

**Shank Diameter:**

0.190 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.302 inches

**End Application:**

V1h-1n helicopter

**Grip Length:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

5380 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-100 degree flush shear head, alloy steel

**Material:**

Steel comp 8740

**Material Specification:**

Mil-s-6049 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 type ii.Class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.