

View Online at <https://aerobasegroup.com/nsn/5320-01-564-2179>

Thread Class:

3a

Thread Direction:

Left-hand

Fastener Length:

Between 1.135 inches and 1.155 inches

Head Style:

Straight pan

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.750 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

9300 double pounds per square inch

Special Features:

Id color coded, black, on threaded end

Material:

Titanium alloy

Material Specification:

Ams 4928 assn standard 1st material response or ams 4967 assn standard 2nd material response

Surface Treatment:

Aluminum alloy

Surface Treatment Specification:

Hi-shear specification 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0