

View Online at <https://aerobasegroup.com/nsn/5320-01-564-2356>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.365 inches and 1.385 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.068 inches and 0.078 inches

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3110 inches and 0.3120 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.475 inches and 0.505 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.875 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Shear Strength:**

14600 double pounds per square inch

**Special Features:**

Id color, black, on threaded end

**Material:**

Titanium alloy

**Material Specification:**

Ams 4928 assn standard 1st material response or ams 4967 assn standard 2nd material response

**Surface Treatment:**

Aluminum alloy

**Surface Treatment Specification:**

Hi-shear specification 294 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0