NSN 5320-01-564-2375

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-564-2375 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.240 inches and 1.260 inches **Head Style:** Straight pan **Head Height:** Between 0.068 inches and 0.078 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.750 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 14600 double pounds per square inch **Special Features:** Id color, black, on threaded end Material: Titanium alloy **Material Specification:** Ams 4928 assn standard 1st material response or ams 4967 assn standard 2nd material response **Surface Treatment:** Aluminum alloy **Surface Treatment Specification:** Hi-shear specification 294 mfr ref single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5320-01-564-2375

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0