

View Online at <https://aerobasegroup.com/nsn/5320-01-564-2403>

**Thread Class:**

3a

**Thread Direction:**

Left-hand

**Fastener Length:**

Between 1.250 inches and 1.270 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.059 inches and 0.069 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2797 inches and 0.2807 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.387 inches and 0.412 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.875 inches

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Shear Strength:**

11800 double pounds per square inch

**Special Features:**

Id color coded, black, on threaded end

**Material:**

Titanium alloy

**Material Specification:**

Ams 4928 assn standard 1st material response or ams 4967 assn standard 2nd material response

**Surface Treatment:**

Aluminum alloy

**Surface Treatment Specification:**

Hi-shear specification 294 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0