
NSN 5320-01-565-3124

Pin-rivet - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.085 inches and 2.005 inches

Head Style:

Straight pan

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.104 inches and 0.119 inches

Shank Diameter:

0.188 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10 aircraft

Grip Length:

Between 0.745 inches and 0.755 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

132000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

7480 double pounds per square inch

Product Name:

Pin-rivet

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2416 assn standard single treatment response

NSN 5320-01-565-3124

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

