

View Online at <https://aerobasegroup.com/nsn/5320-01-566-2189>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.053 inches and 2.073 inches

Head Style:

Straight pan

Head Height:

Between 0.102 inches and 0.112 inches

Width Between Flats:

Between 0.160 inches and 0.180 inches

Shank Diameter:

Between 0.311 inches and 0.312 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.475 inches and 0.505 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10 aircraft

Grip Length:

Between 1.558 inches and 1.568 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Product Name:

Hi-lok, hi-tigue pin, protruding tension head

Material:

Steel comp 630

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-kote 1 aluminum coating per hi-shear specification 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0