

View Online at <https://aerobasegroup.com/nsn/5320-01-566-2189>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.053 inches and 2.073 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.102 inches and 0.112 inches

**Width Between Flats:**

Between 0.160 inches and 0.180 inches

**Shank Diameter:**

Between 0.311 inches and 0.312 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.475 inches and 0.505 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

A-10 aircraft

**Grip Length:**

Between 1.558 inches and 1.568 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Product Name:**

Hi-lok, hi-tigue pin, protruding tension head

**Material:**

Steel comp 630

**Material Specification:**

Ams5662 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Hi-kote 1 aluminum coating per hi-shear specification 294 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0