NSN 5320-01-567-3432

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-567-3432

Thread Class:				
3a				
Thread Direction:				
Right-hand				
Fastener Length:				
Between 2.573 inches and 2.593 inches				
Head Style:				
Flush countersunk				
Width Between Flats:				
Between 0.122 inches and 0.142 inches				
Shank Diameter:				
Between 0.248 inches and 0.250 inches				
Shank Style:				
Pin-rivet, straight, threaded				
Head Major Diameter:				
Between 0.501 inches and 0.507 inches				
Lubrication:				
Cetyl alcohol, specification 305, hi-shear corp				
End Application:				
A-10 aircraft				
Grip Length:				
Between 2.183 inches and 2.193 inches				
Thready Qty Per Inch (tpi):				
28				
Min. Tensile Strength (psi):				
160000 pounds per square inch				
Thread Size:				
0.250 inches				
Shear Strength:				
9300 double pounds per square inch				
Countersink Angle:				
100.0 degrees				
Material:				
Steel comp 8740				
Material Specification:				
Ams6049 assn standard single material response				
Surface Treatment:				
Cadmium				
Surface Treatment Specification:				
Ams-qq-p-416, type ii.Class 2 assn standard single treatment response				
Thread Series Designator:				

Unjf

NSN 5320-01-567-3432

Pin-rivet - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0