NSN 5320-01-567-3471

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-567-3471 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.760 inches and 1.780 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.122 inches and 0.142 inches **Shank Diameter:** Between 0.248 inches and 0.250 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.501 inches and 0.507 inches **End Application:** A-10 aircraft **Grip Length:** Between 1.370 inches and 1.380 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 9300 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 8740 **Material Specification:** Ams6049 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams-qq-p-35, type ii.Class 2 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5320-01-567-3471

Pin-rivet - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A528u0