NSN 5320-01-567-3915

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-567-3915

| View Online at https://aerobasegroup.com/nsn/5320-01-567-3915 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Fastener Length: |
| Between 2.510 inches and 2.530 inches |
| Head Style: |
| Straight pan |
| Head Height: |
| Between 0.077 inches and 0.090 inches |
| Width Between Flats: |
| 0.122 mils and 0.142 centimeters |
| Shank Diameter: |
| Between 0.264 inches and 0.266 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.415 inches and 0.440 inches |
| Lubrication: |
| Cetyl alcohol, specification 305, hi-shear corp |
| End Application: |
| A-10 aircraft |
| Grip Length: |
| 2.120 mils and 2.130 centimeters |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Thread Size: |
| 0.250 inches |
| Shear Strength: |
| 10490 double pounds per square inch |
| Material: |
| Steel comp 8740 |
| Material Specification: |
| Ams-s-6049 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Ams-p-qq-p-416, type ii.Class 2 assn standard single treatment response |
| Thread Series Designator: |
| 11.25 |

Unjf

NSN 5320-01-567-3915

Pin-rivet - Page 2 of 2



| _ | | | - | | |
|---|----|----|---|------|---|
| C | hο | 14 | | .ife | • |
| • | | | _ | .116 | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0