

View Online at <https://aerobasegroup.com/nsn/5320-01-567-4354>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.760 inches and 2.780 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.077 inches and 0.090 inches

**Width Between Flats:**

Between 0.122 inches and 0.142 inches

**Shank Diameter:**

Between 0.248 inches and 0.250 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.415 inches and 0.440 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

A-10 aircraft

**Grip Length:**

Between 2.370 inches and 2.380 inches

**Thready Qty Per Inch (tpi):**

28

**Minimum Yield Strength:**

160000 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

9300 double pounds per square inch

**Material:**

Steel comp 8740

**Material Specification:**

Ams6049 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams-qq-p-416, type ii.Class 2 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0