

View Online at <https://aerobasegroup.com/nsn/5320-01-567-4456>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.823 inches and 2.843 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.122 inches and 0.143 inches

Shank Diameter:

Between 0.264 inches and 0.266 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.501 inches and 0.507 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10 aircraft

Grip Length:

Between 2.433 inches and 2.443 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

10490 double pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 8740

Material Specification:

Mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii. Class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.