NSN 5320-01-567-4481

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-567-4481

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 2.698 inches and 2.718 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.122 inches and 0.142 inches
Shank Diameter:
Between 0.248 inches and 0.250 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.501 inches and 0.507 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
End Application:
A-10 aircraft
Grip Length:
Between 2.308 inches and 2.318 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
9300 double pounds per square inch
Countersink Angle:
100.0 degrees
Material:
Steel comp 8740
Material Specification:
Ams6049 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Ams-qq-p-416, type ii.Class 2 assn standard single treatment response
Thread Series Designator:

Unjf

NSN 5320-01-567-4481

Pin-rivet - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0