

View Online at <https://aerobasegroup.com/nsn/5320-01-567-4515>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.565 inches and 0.585 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.104 inches and 0.119 inches

Shank Diameter:

Between 0.189 inches and 0.190 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.376 inches and 0.382 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

B1-b aircraft

Grip Length:

Between 0.245 inches and 0.255 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

7060 double pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Per hishear spec. 262 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0