

View Online at <https://aerobasegroup.com/nsn/5320-01-567-7052>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.769 inches and 2.789 inches

Head Style:

Straight pan

Head Height:

Between 0.178 inches and 0.188 inches

Width Between Flats:

Between 0.269 inches and 0.289 inches

Shank Diameter:

Between 0.498 inches and 0.500 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.717 inches and 0.752 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10 aircraft

Grip Length:

Between 2.089 inches and 2.099 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.500 inches

Shear Strength:

37300 double pounds per square inch

Product Name:

Pin-riquet

Material:

Steel comp 8740

Material Specification:

Ams-s-6049 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams-qq-p-35 type ii.Class 2 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0