

View Online at <https://aerobasegroup.com/nsn/5320-01-567-7101>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.604 inches and 2.624 inches

Head Style:

Straight pan

Head Height:

Between 0.077 inches and 0.090 inches

Width Between Flats:

Between 0.122 inches and 0.142 inches

Shank Diameter:

Between 0.264 inches and 0.266 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10 aircraft

Grip Length:

Between 2.214 inches and 2.224 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

10490 double pounds per square inch

Product Name:

Pin-rivet

Material:

Steel comp 8740

Material Specification:

Ams-s-6049 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams-p-416, type ii.Class 2 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0