

View Online at <https://aerobasegroup.com/nsn/5320-01-568-2858>

Fastener Length:

0.781 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.310 inches and 0.312 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.333 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.531 inches and 0.595 inches

Min. Tensile Strength (psi):

36500 pounds per square inch

Hardness Rating:

48.0 rockwell c stem

Shear Strength:

5900 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel sleeve

Material Specification:

66 federal standard 1st material response mechanical lock or ams a286 assn standard 2nd material response mechanical lock or ams 5737 assn standard 3rd material response mechanical lock or ams 5690 assn standard 4th material response mechanical lock

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-c-83488 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-83488 spec.