## NSN 5320-01-568-4364

Threaded Pin-rivet - Page 1 of 1

**Unit Of Measure:** 

**Demilitarization:** 

No



View Online at https://aerobasegroup.com/nsn/5320-01-568-4364 Fastener Length: 0.820 inches **Head Height:** Between 0.059 inches and 0.069 inches **Shank Diameter:** 0.250 inches Lubrication: Cetyl alcohol **Grip Length:** 0.500 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.2500 inches **Shear Strength:** 125000 single pounds per square inch **Product Name:** Pin, protruding, shear head, ph13-8mo cres, hex drive **Special Features:** Material: ph13-8mo cres per ams5629, heat treat: 125, 000 psi shear per ams2759, finish: aluminum pigmented coating per specification 294 or nas4006, lubricants: cetyl alcohol lube per specification 305 Material: Stainless steel **Surface Treatment:** Aluminum **Special Test Features:** Pin-protruding shear head, cres .250" diameter, .2500-28 thread, .500" grip length, cetyl alcohol lube, aluminum coated weight = 6.656 + (8x.849) = 13.448lb per 1,000 pieces**Thread Series Designator:** Unjf Shelf Life: N/a