

View Online at <https://aerobasegroup.com/nsn/5320-01-569-3645>

Thread Class:

3a

Thread Direction:

Right-hand

Head Style:

Straight pan

Head Height:

Between 0.080 inches and 0.090 inches

Shank Diameter:

Between 0.249 inches and 0.250 inches

Shank Style:

Pin-riquet, tapered, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Tip Diameter:

Between 0.241 inches and 0.244 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

1680-01-561-7258

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

210000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

125000 single pounds per square inch

Product Name:

Pin, hi-lok

Special Features:

Length of item is 2.000 inch

Material:

Nickel alloy

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0