

View Online at <https://aerobasegroup.com/nsn/5320-01-569-3645>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Head Style:**

Straight pan

**Head Height:**

Between 0.080 inches and 0.090 inches

**Shank Diameter:**

Between 0.249 inches and 0.250 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

Between 0.415 inches and 0.440 inches

**Tip Diameter:**

Between 0.241 inches and 0.244 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

1680-01-561-7258

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

210000 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

125000 single pounds per square inch

**Product Name:**

Pin, hi-lok

**Special Features:**

Length of item is 2.000 inch

**Material:**

Nickel alloy

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, ty ii, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0