

View Online at <https://aerobasegroup.com/nsn/5320-01-571-5269>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.780 inches and 0.800 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.104 inches and 0.119 inches

**Shank Diameter:**

Between 0.189 inches and 0.190 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.382 inches and 0.392 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

Rq-4a

**Grip Length:**

Between 0.495 inches and 0.505 inches

**Thread Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

5380 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A528u0