# NSN 5320-01-571-5269

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-571-5269



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.780 inches and 0.800 inches

### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.104 inches and 0.119 inches

#### Shank Diameter:

Between 0.189 inches and 0.190 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.382 inches and 0.392 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

### **End Application:**

Rq-4a

# Grip Length:

Between 0.495 inches and 0.505 inches

# Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

95000 pounds per square inch

## Thread Size:

0.190 inches

### Shear Strength:

5380 double pounds per square inch

### Countersink Angle:

100.0 degrees

#### Material:

Titanium alloy uns r56400

### Material Specification:

Ams4928 assn standard single material response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-571-5269

Pin-rivet - Page 2 of 2

# Demilitarization:

Yes - demil/mli

Fiig:

A528u0

