## NSN 5320-01-571-6142

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-571-6142 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.622 inches and 0.642 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.122 inches and 0.142 inches **Shank Diameter:** Between 0.249 inches and 0.250 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.502 inches and 0.512 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** Rq-4a **Grip Length:** Between 0.307 inches and 0.317 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 5320-01-571-6142

Pin-rivet - Page 2 of 2



Fiig:

A528u0