NSN 5320-01-571-6146

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-571-6146



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.185 inches and 1.205 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.122 inches and 0.142 inches

Shank Diameter:

Between 0.249 inches and 0.250 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.502 inches and 0.512 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

Grq-4a

Grip Length:

Between 0.870 inches and 0.880 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

95000 pounds per square inch

Thread Size:

0.250 inches

Countersink Angle:

100.0 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5320-01-571-6146

Pin-rivet - Page 2 of 2

Fiig: A528u0

