## NSN 5320-01-571-6956

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-571-6956 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.562 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.160 inches and 0.180 inches **Shank Diameter:** Between 0.311 inches and 0.312 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.133 inches and 0.135 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.062 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 14800 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Grit blast top of head, light blue on thread Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-571-6956

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0